



The perfect partner when you cook

The 6000 Hob2Hood® Cooker Hood wirelessly connects to the hob. The lights activate when you turn on the hob, and the fan speed is regulated based on the heat setting on the hob. Experience an odour-free kitchen every time you cook.

Product Benefits & Features

Hob2Hood®. The perfect partner when you cook.

The Hob2Hood® function wirelessly activates the hood lights when you turn on the hob. When you start cooking, the fan speed is regulated based on the heat settings on the hob. Cook delicious meals without worrying about odours and vapours.



ExtractionTech Pro cooker hood: High power, exceptional freshness

Experience superior kitchen air quality with the ExtractionTech Pro cooker hood. Equipped with our most powerful motor and intensive speed option, it efficiently extracts cooking vapours ensuring an exceptionally fresh cooking environment.



Spotlight the details with the Pure Illumination

Energy-efficient Pure Illumination provides full visibility while cooking. The LED lights illuminate the entire cooking surface, making it easy to see every detail of your meal preparation.




Reliable, easy-to-clean grease filter keeps kitchen fresh

Convenient, reliable grease filter ensures your kitchen stays fresh and hood performs at its best. Wash by hand or in dishwasher.



Filter cleaning notification system

The hood has a convenient filter cleaning notification system. An indicator on the hood alerts you when the grease filter and carbon filter need cleaning – there's no need to keep track of it yourself.



- Air extraction capacity (high/low): 580 / 300 m³/h
- Max. extraction capacity (intensive): 700 m³/h
- Number of speeds: 3+Intensive
- Cooker hood lamps type and number: LED spotlight, 2
- Edge extraction
- Operation via buttons
- Grease filter indicator.
- Charcoal filter indicator.
- Grease filter type and number: Aluminium mesh, 2
- Air extraction or recirculation possible, charcoal filter included.
- Remote control MECH06, PNC 902 980 072 available as an optional extra.

Product Specification

Energy Rating	A	Intensive Recirculated Extraction Rate (m³/h)	435
Number of Speed Settings	3+Intensive	Series	6000
Installation Type	Group	Dimensions, HxWxD	-331x770x300
Size (cm)	80	Frequency (Hz)	50
Extraction Type - Recirculation	Yes	Superperforming charcoal filter compatible	NO, NO
Extraction Type - Ducted (External)	Yes	Product Number (PNC)	E - Generic Partner All
Minimum Distance from Electric Hob (cm)	50	Plug or Hardwired	Hardwired connection only
Minimum Distance from Gas Hob (cm)	57		
Cord Length (m)	1.8		
Voltage (V)	220-240		
Required Fuse (A)	No		
Charcoal Filter Type	ECFB01ST		
Fluid Dynamic Efficiency Rating	A		
Lighting Efficiency Rating	A		
Grease Filter Efficiency Rating	D		
Lamp Type	LED spotlight		
Number of Lights	2		
Number of Grease Filters	2		
Min Recirculated Noise Level (dB)	62		
Max Recirculated Noise Level (dB)	74		
Min Recirculated Extraction Rate (m³/h)	295		
Max Recirculated Extraction Rate (m³/h)	430		

