



The perfect partner when you cook

The 6000 Hob2Hood® Cooker Hood wirelessly connects to the hob. The lights activate when you turn on the hob, and the fan speed is regulated based on the heat setting on the hob. Experience an odour-free kitchen every time you cook.

Powered by an energy-efficient motor, this well-designed chimney hood is installed against the wall, effectively reduces kitchen odours while adding to the look and feel of the space itself.

Product Benefits & Features

Hob2Hood®. The perfect partner when you cook.

The Hob2Hood® function wirelessly activates the hood lights when you turn on the hob. When you start cooking, the fan speed is regulated based on the heat settings on the hob. Cook delicious meals without worrying about odours and vapours.



ExtractionTech Plus: High-performance odour removal

ExtractionTech Plus keeps your kitchen smelling fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.



Spotlight the details with the Pure Illumination

Energy-efficient Pure Illumination provides full visibility while cooking. The LED lights illuminate the entire cooking surface, making it easy to see every detail of your meal preparation.




Reliable, easy-to-clean grease filter keeps kitchen fresh

Convenient, reliable grease filter ensures your kitchen stays fresh and hood performs at its best. Wash by hand or in dishwasher.



Filter cleaning notification system

The hood has a convenient filter cleaning notification system. An indicator on the hood alerts you when the grease filter and carbon filter need cleaning – there's no need to keep track of it yourself.



- Air extraction capacity (high/low): 352 / 175 m³/h
- Max. extraction capacity (intensive): 779 m³/h
- Number of speeds: 3+Intensive; Breeze function
- Cooker hood lamps type and number: LED spotlight, 2
- Control type: Electronic touch controls with 3+Intensive; Breeze function speeds.
- Operation via TouchControl sensors
- Grease filter indicator.
- Charcoal filter indicator.
- Grease filter type and number: Stainless steel design filter, 1
- Air extraction or recirculation possible, charcoal filter included.

Product Specification

Energy Rating	A	Intensive Recirculated Extraction Rate (m³/h)	524
Number of Speed Settings	3+Intensive; Breeze function	Series	6000
Installation Type	Chimney	Dimensions, HxWxD	665-1175x598x500
Size (cm)	60	Frequency (Hz)	50
Extraction Type - Recirculation	Yes	Other comments technical specifications	IN RECIRCULATION: Height min.-max. external, mm 730-1175mm LONG LIFE FILTER TYPE20 IS AVAILABLE AS ACCESSORY
Extraction Type - Ducted (External)	Yes	Superperforming charcoal filter compatible	SUPCHARE22, 902 980 429
Minimum Distance from Electric Hob (cm)	50	Chimney denomination	n/a
Minimum Distance from Gas Hob (cm)	65	Product Number (PNC)	B - Open All
Cord Length (m)	1.5	Plug or Hardwired	Hardwired connection only
Voltage (V)	220-240		
Required Fuse (A)	4		
Charcoal Filter Type	MCFE01ST		
Fluid Dynamic Efficiency Rating	A		
Lighting Efficiency Rating	A		
Grease Filter Efficiency Rating	C		
Lamp Type	LED spotlight		
Number of Lights	2		
Number of Grease Filters	1		
Min Recirculated Noise Level (dB)	44		
Max Recirculated Noise Level (dB)	62		
Min Recirculated Extraction Rate (m³/h)	127		
Max Recirculated Extraction Rate (m³/h)	302		

