



The perfect partner when you cook

The 6000 Hob2Hood® Cooker Hood wirelessly connects to the hob. The lights activate when you turn on the hob, and the fan speed is regulated based on the heat setting on the hob. Experience an odour-free kitchen every time you cook.

Powered by an energy-efficient motor, this well-designed chimney hood is installed against the wall, effectively reduces kitchen odours while adding to the look and feel of the space itself.

Product Benefits & Features



Natural air, effortlessly and silently.

The sleekly designed AEG hood removes lingering odours quietly thanks to a super quiet breeze technology. So you can have a better environment in your kitchen effortlessly and silently.



The hands-free hood

This cooker hood has Hob2Hood, a useful feature that automatically controls your cooker hood and lights. Leave Hob2Hood to regulate the fan while you concentrate on the key moments involved in getting your dish just right. But if you'd rather adjust the fan speed yourself, there

Clean air with less energy

A strong motor with low-energy consumption means this hood is reliable and efficiently clears away kitchen odours.

Clean air. Designed to last

This filter captures and cleans away cooking smells incredibly efficiently to leave kitchens fresh. The longest-lasting disposable filter, it can be washed and reactivated to ensure it maintains its high odour-filtering performance.



All cooking vapours removed – in silence

Thanks to innovative technology, this hood clears your kitchen of unwanted cooking vapours almost unnoticeably. What's more, the cooker hood's virtually silent operation helps you create the perfect atmosphere in your home.

- Air extraction capacity (high/low): 352 / 175 m³/h
- Max. extraction capacity (intensive): 779 m³/h
- Number of speeds: 3+Intensive; Breeze function
- Cooker hood lamps type and number: LED spotlight, 2
- Control type: Electronic touch controls with 3+Intensive; Breeze function speeds.
- Operation via TouchControl sensors
- Grease filter indicator.
- Charcoal filter indicator.
- Grease filter type and number: Stainless steel design filter, 2
- Air extraction or recirculation possible, charcoal filter included.

Product Specification

Energy Rating	A	Intensive Recirculated Extraction Rate (m³/h)	524
Number of Speed Settings	3+Intensive; Breeze function	Series	6000
Installation Type	Chimney	Dimensions, HxWxD	665-1175x898x500
Size (cm)	90	Frequency (Hz)	50
Extraction Type - Recirculation	Yes	Other comments technical specifications	SilenceTech model (max speed not higher then 54 dBA)
Extraction Type - Ducted (External)	Yes		IT IS POSSIBLE TO INSTALL ALSO LONG LIFE FILTER -> TYPE20 942 121 993
Minimum Distance from Electric Hob (cm)	50		IN RECIRCULATION: Height min.-max. external, mm 730-1175mm
Minimum Distance from Gas Hob (cm)	65		
Cord Length (m)	1.5	Superperforming charcoal filter compatible	SUPCHARE22, 902 980 429
Voltage (V)	220-240	Chimney denomination	n/a
Required Fuse (A)	4	Product Number (PNC)	B - Open All
Charcoal Filter Type	MCFE01ST	Plug or Hardwired	Uk Moulded Plug
Fluid Dynamic Efficiency Rating	A		
Lighting Efficiency Rating	A		
Grease Filter Efficiency Rating	C		
Lamp Type	LED spotlight		
Number of Lights	2		
Number of Grease Filters	2		
Min Recirculated Noise Level (dB)	44		
Max Recirculated Noise Level (dB)	62		
Min Recirculated Extraction Rate (m³/h)	127		
Max Recirculated Extraction Rate (m³/h)	302		

