



Experience fresher, cleaner kitchen air. Every day

The 3000 ExtractionTech Standard hood features a reliable motor for effective odour extraction while preparing meals. Your kitchen air remains fresh and clean for a better cooking experience, everyday.

Hidden in the unit over the hob, this discreet hood is only visible when it needs to be; it can be smoothly flipped open to activate the extractor while cooking and then pushed back into place when idle.

Product Benefits & Features



Keep the kitchen fresh with the ExtractionTech Standard hood.

The ExtractionTech Standard hood features a reliable motor for effective odour extraction while preparing meals. Your kitchen environment remains fresh and clean for a better cooking experience, everyday.



Spotlight the details with the Pure Illumination

Energy-efficient Pure Illumination provides full visibility while cooking. The LED lights illuminate the entire cooking surface, making it easy to see every detail of your meal preparation.



Reliable, easy-to-clean grease filter keeps kitchen fresh

Convenient, reliable grease filter ensures your kitchen stays fresh and hood performs at its best. Wash by hand or in dishwasher.

- Air extraction capacity (high/low): 370 / 235 m³/h
- Number of speeds: 3
- Cooker hood lamps type and number: LED bulb, 2
- Variable electronic speed control - easy to use
- Grease filter type and number: Aluminium Cassette, 2
- Air extraction or recirculation possible, charcoal filter included.

Product Specification

Energy Rating	D	Series	3000
Number of Speed Settings	3	Dimensions, HxWxD	400-400x598x270
Installation Type	Integrated	Frequency (Hz)	50/60
Size (cm)	60	Other comments technical specifications	Out of scope for ecodesign regulation.
Extraction Type - Recirculation	Yes	Superperforming charcoal filter compatible	NO, NO
Extraction Type - Ducted (External)	Yes	Product Number (PNC)	B - Open All
Minimum Distance from Electric Hob (cm)	50	Plug or Hardwired	Hardwired connection only
Minimum Distance from Gas Hob (cm)	70		
Cord Length (m)	1.5		
Voltage (V)	220-240		
Required Fuse (A)	4		
Charcoal Filter Type	MCFE21ST		
Fluid Dynamic Efficiency Rating	E		
Lighting Efficiency Rating	A		
Grease Filter Efficiency Rating	C		
Lamp Type	LED bulb		
Number of Lights	2		
Number of Grease Filters	2		
Min Recirculated Noise Level (dB)	62		
Max Recirculated Noise Level (dB)	67		
Min Recirculated Extraction Rate (m³/h)	222		
Max Recirculated Extraction Rate (m³/h)	266		

