



The perfect partner when you cook

The 6000 Hob2Hood® Cooker Hood wirelessly connects to the hob. The lights activate when you turn on the hob, and the fan speed is regulated based on the heat setting on the hob. Experience an odour-free kitchen every time you cook.

Product Benefits & Features

Hob2Hood®. The perfect partner when you cook.

The Hob2Hood® function wirelessly activates the hood lights when you turn on the hob. When you start cooking, the fan speed is regulated based on the heat settings on the hob. Cook delicious meals without worrying about odours and vapours.



High Performance Motor. Always fresh kitchen air

Elevate your kitchen atmosphere with the High Performance Motor. Its powerful engine swiftly eliminates cooking odours, leaving your kitchen smelling fresh and clean.




Filter cleaning notification system

The hood has a convenient filter cleaning notification system. An indicator on the hood alerts you when the grease filter and carbon filter need cleaning – there's no need to keep track of it yourself.



LED Strip – put your cooking in the best light

Illuminate your culinary space with long-lasting LED Strip lighting. Benefit from improved visibility and ambient lighting when cooking your favourite dish with efficient lighting.



Quick and reliable PerfectFit Installation

For fast & accurate PerfectFit Installation of your new cooker hood. It's our Best-In-Class Installation with fewer mounting steps compared to previous models, it provides a user-friendly experience, making the work an easy one-person job fitting in all standard niches.



- Air extraction capacity (high/low): 445 / 260 m³/h
- Max. extraction capacity (intensive): 750 m³/h
- Number of speeds: 3+Intensive
- Cooker hood lamps type and number: LED stripe, 1
- Control type: Electronic touch controls with 3+Intensive speeds.
- Operation via TouchControl sensors
- Grease filter indicator.
- Charcoal filter indicator.
- Grease filter type and number: Stainless steel design filter, 1
- Extraction or recirculation mode possible, charcoal filter available as optional accessory for recirculation operation

Product Specification

Energy Rating	A	Intensive Recirculated Extraction Rate (m³/h)	590
Number of Speed Settings	3+Intensive	Series	6000
Installation Type	Integrated	Dimensions, HxWxD	330-330x600x308
Size (cm)	60	Frequency (Hz)	50
Extraction Type - Recirculation	Yes	Other comments technical specifications	spacers included in the product for different depths of cabinets--> Depht min: 308, Depht max:348 // Exstention with chimney (accessory)--> Height min:626 Height max:900
Extraction Type - Ducted (External)	Yes		
Minimum Distance from Electric Hob (cm)	50	Superperforming charcoal filter compatible	NO, NO
Minimum Distance from Gas Hob (cm)	65	Chimney denomination	MECK54
Cord Length (m)	1.4	Product Number (PNC)	B - Open All
Voltage (V)	230-240	Plug or Hardwired	Hardwired connection only
Required Fuse (A)	No		
Charcoal Filter Type	NO		
Fluid Dynamic Efficiency Rating	A		
Lighting Efficiency Rating	A		
Grease Filter Efficiency Rating	B		
Lamp Type	LED stripe		
Number of Lights	1		
Number of Grease Filters	1		
Min Recirculated Noise Level (dB)	54		
Max Recirculated Noise Level (dB)	69		
Min Recirculated Extraction Rate (m³/h)	225		
Max Recirculated Extraction Rate (m³/h)	440		

